



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: **A**

Revision Date:
07/06/2023

Authored by: J.Anderson

Approved by: K.Plunkett

A) DESCRIPTION

The HD Retrievable Packer is a heavy duty service packer ideally suited for all types of squeeze cementing, formation fracturing, high pressure acidizing, etc. It is a large opening compression set packer with hydraulic button-type hold down. This packer withstands high pressure from above or below and uses a 3-element packing system, J-slot, and a drag block mechanism for easy setting. This packer has a built-in unloader which circulates across the hold down buttons to improve retrievability and run in performance.

B) SPECIFICATION GUIDE

CASING			TOOL		THREAD CONNECTION BOX UP / PIN DOWN	PART NUMBER
SIZE (INCHES)	WEIGHT (LBS/FT)	RECOMMENDED HOLE SIZE (INCHES)	GAGE OD (INCHES)	ID (INCHES)		
6	24.5	5.200	5.000	2.00	2-3/8 EUE	61362XLS 61362XLSH ¹ 61362XLSV ²

Elastomer Trim Options: ¹HSN, ²Viton

NOTE1: Tools listed are left-hand auto set / straight pick-up.

DIFFERENTIAL PRESSURE (MAX)	TENSILE LOAD THRU UNSET TOOL (MAX)	HANGING WEIGHT ON SET TOOL (MAX)*	TORQUE THRU TOOL (MAX)
10,000 PSI	73,500 LBS	73,500 LBS	2,000 FT-LBS

*Casing must be cemented for this load rating.

CAUTION1: Before running the tool, check the pressure affected areas chart and consider other effects to be certain that the unloader will remain closed during operation.

CAUTION2: If the HD Packer is run with a retrievable bridge plug, make sure the bridge plug J-slot is compatible with the J-slot on the packer. Whichever direction you set the plug, the packer should set in the **opposite** direction.

C) PRE-INSTALLATION INSPECTION PROCEDURES

CAUTION3: D&L ships tool connections made-up hand-tight—labeled with hand-tight tape on the tool—unless stated otherwise. Properly tighten connections before operating tool (Fig. 1).



Fig. 1

GENERAL THREAD CONNECTION TORQUE RECOMMENDATIONS			
STUB ACME / ACME THREADS	INTERNAL TAPERED TUBING THREADS		PREMIUM THREADS
	UP TO 2-3/8"	GREATER THAN 2-3/8"	
600 – 800 FT-LBS	600 – 800 FT-LBS	800 – 1,200 FT-LBS	Consult thread manufacturer's recommendations.

D & L OIL TOOLS
P.O. BOX 52220 TULSA, OK 74152
PHONE: (800) 441-3504 www.dloiltools.com



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: **A**

Revision Date:
07/06/2023

Authored by: *J.Anderson*

Approved by: *K.Plunkett*

C) PRE-INSTALLATION INSPECTION PROCEDURES (cont'd)

GENERAL SCREW TORQUE RECOMMENDATIONS									
SCREW SIZE (INCHES)	#6	#8	#10	1/4	5/16	3/8	7/16	1/2	5/8 and larger
TORQUE RANGE (INCH-POUNDS)	5 – 8	10 – 15	18 – 25	25 – 40	50 – 80	90 – 135	160 – 210	250 – 330	450 - 650

Before first use, D&L recommends disassembly and inspection of the tool unless stated otherwise. Ensure parts have not been damaged during shipping. Replace damaged parts with D&L replacement parts. Contact D&L sales for replacement part information.

Re-assemble the tool after inspection. Install parts in the correct order and orientation. Properly tighten connections.

Before re-using the tool, D&L recommends disassembly and inspection of the tool. Clean parts and ensure parts are in good working condition. Replace worn or damaged parts with D&L replacement parts.

When redressing the tool, D&L recommends replacement of all seals, elements, o-rings, shear screws, etc. Contact D&L sales for redress kit and/or other replacement part information.

D) SETTING PROCEDURES

CAUTION4: Do not run the tool without properly tightening connections. Running the tool with loose connections may damage the tool and cause malfunction.

Run to setting depth. The unloader remains open while running in. Pick up the work string and rotate 1/4 left-hand turn at the packer. Slack off weight and set down on the packer to set the slips, close the unloader and compress the packing elements. A minimum weight of 12,000 lbs. at the packer is required to pack off the elements.

CAUTION5: Run the tool slowly, as with any hold down type packer, to help prevent dulling of the hydraulic buttons.

E) RELEASING PROCEDURES

Pick up on the work string to open the unloader, allowing time for the tubing and casing pressure to equalize. Refer to Pressure Affected Area Guide to determine weight in addition to pipe weight required to pick up on packer. Continued upward movement of the work string unsets the slips, relaxes the packing elements and re-jays the packer. The tool may now be moved and reset, or pulled from the well.

F) STORAGE RECOMMENDATIONS

When preparing the tool for storage, follow the Pre-Installation Inspection Procedures. Re-assemble the tool with connections hand-tight only and in running position if applicable. Elastomers should be in a relaxed state—free from tension, compression, and other stresses that could cause deformation.

Store the tool, if possible, in an enclosed, temperature and humidity controlled environment. Avoid excessively high temperatures over long periods of time. Shield elastomeric parts from ultraviolet light sources. Keep tool dry and protected from condensation. Do not store in contact with or near volatile or corrosive chemicals. Do not store near ozone generating equipment or operations such as welding.



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: **A**

Revision Date:
07/06/2023

Authored by: J.Anderson

Approved by: K.Plunkett

G) PRESSURE AFFECTED AREA GUIDE

When set downhole, the packer mandrel is subjected to a force created by differential pressure above or below the packer that acts on the pressure affected area (i.e., the piston effect). Depending on the tubing size and weight and the seal area of the packer the force created by differential pressure acts upwards or downwards on the packer mandrel. An upward force, designated as a negative (-) value, acts to push the packer mandrel up hole and must be accounted for to ensure that the packer remains set. A downward force, designated as a positive value, acts to push the packer mandrel down hole and must be accounted for when releasing the packer. Other factors (e.g., tubing movement due to temperature change) must be considered separately to determine all the forces acting on the packer.

PACKER SIZE (IN)	TUBING TO PACKER			PRESSURE AFFECTED AREA (IN ²)			
	SIZE (IN)	WEIGHT (LBS/FT)	ID (IN)	ABOVE		BELOW	
6	1.900	2.40	1.650	1.150	(DOWN)	2.424	(DOWN)
		2.90	1.610	1.150	(DOWN)	2.322	(DOWN)
	2.375	4.00	2.041	-0.445	(UP)	3.557	(DOWN)
		4.70	1.995	-0.445	(UP)	3.412	(DOWN)
		5.95	1.867	-0.445	(UP)	3.023	(DOWN)
	2.875	6.50	2.441	-2.507	(UP)	4.965	(DOWN)
		7.90	2.323	-2.507	(UP)	4.524	(DOWN)
		8.70	2.259	-2.507	(UP)	4.294	(DOWN)
	3.500	7.70	3.068	-5.636	(UP)	7.678	(DOWN)
		9.30	2.992	-5.636	(UP)	7.317	(DOWN)
		10.20	2.922	-5.636	(UP)	6.991	(DOWN)
		12.95	2.750	-5.636	(UP)	6.225	(DOWN)
	4.000	9.50	3.548	-8.581	(UP)	10.173	(DOWN)
		11.00	3.476	-8.581	(UP)	9.775	(DOWN)
	4.500	12.75	3.958	-11.919	(UP)	12.590	(DOWN)

Example: Consider a 6" X 2-3/8" HD Packer set on 2.375" (4.70 lbs/ft) tubing with a differential pressure of 3,000 PSI in the annulus around the tubing above the packer. What is the force acting on the seal area of the mandrel?

To calculate the force (lbs) acting on the seal area of the mandrel, refer to the Pressure Affected Area Guide for a 6" X 2-3/8" HD Packer run on 2.375" (4.70 lbs/ft) tubing. In this example, the differential pressure from above the packer acts on the seal area of the packer mandrel across a pressure affected area of -0.445 in². Multiplying the differential pressure (3,000 PSI) by the pressure affected area (-0.445 in²) results in a force of -1,335 lbs. The piston effect on the packer mandrel is an upward force of 1,335 lbs.

H) ELASTOMER TRIM TEMPERATURE GUIDE

NITRILE (STD)			
TEMPERATURE RANGE (F°)	DUROMETER		
	END	MIDDLE	END
40° - 125°	80	70	80
125° - 250°	90	70	90
150° - 250°	90	80	90
250° +	Contact D&L Sales		

RUBBER TYPE	TEMPERATURE RANGE
NITRILE	40° - 250°F
HSN (HNBR)	70° - 300°F
VITON	100° - 350°F



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: **A**

Revision Date:
07/06/2023

Authored by: J.Anderson

Approved by: K.Plunkett

I) RECOMMENDED TOOLS

I-1) HAND TOOLS

- VISE
- GLOVES
- ALLEN WRENCHES
- TAPE MEASURE
- O-RING PICK
- BAR
 - 1/2-INCH
 - 3/4-INCH
- PAINT BRUSH, 2-INCH
- PIPE WRENCH, 3-FT (2 EA)
- "CHEATER" PIPE, 4-FT LONG
- ADJUSTABLE WRENCH, 12-INCH
- CORDLESS DRILL, 18V
- SNAP RING SPREADER PLIERS
- ALIGNING PUNCH
- SCREWDRIVER SET, FLAT-TIPPED
- SOCKET SETS
 - 3/8-INCH DRIVE
 - 1/2-INCH DRIVE
- HAMMERS
 - SLEDGE
 - BALL PEEN
 - DEAD BLOW

I-2) SPECIAL TOOLS

ITEM	QTY	DESCRIPTION	PART NUMBER
T1	1	DRAG BLOCK ASSEMBLY TOOL	AT055110
T2	1	BUTTON REMOVAL TOOL	AT-BRT000
T3	1 GAL	KOPR-KOTE® ANTI-SEIZE LUBRICANT	DL-KOPR-KOTE-1G

J) DISASSEMBLY

J-1) Clamp top sub (1) in vise.

- J-1.1) Unscrew and remove set screws (37) from bottom sub (23). Move J-body (20) as needed to access set screws (31).
- J-1.2) Unscrew and remove bottom sub (23) from inner mandrel (2).
NOTE₃: Drag block body assembly must be free to rotate.
 J-1.2.1) Remove o-ring (39) from bottom sub (23).
- J-1.3) Compress drag blocks (22) with drag block assembly tool (T1).
- J-1.4) Unscrew and remove set screws (35) from J-body (20).
- J-1.5) Unscrew and remove J-body (20) from drag block body (18) (**NOTE₄**: Left-hand threads).
- J-1.6) Remove drag block retainer (21) from drag block body (18).
- J-1.7) Release drag blocks (22). Remove drag blocks (22) and drag block springs (3) from drag block body (18).
- J-1.8) Unscrew and remove rubber mandrel cap (19) from rubber mandrel (11).
NOTE₅: For added leverage, insert a rod through rubber retainer (15) and rubber mandrel (11) as needed.
- J-1.9) Remove drag block body assembly and disassemble:
 J-1.9.1) Unscrew and remove socket cap screw (34) from drag block body (18).
 J-1.9.2) Wedge lower slips (17) outward (if needed). Remove lower slip support (32) from drag block body (18).
 J-1.9.3) Remove wedges (if needed). Remove lower slips (17) and lower slip springs (25) from drag block body (18).
- J-1.10) Unscrew and remove lower cone (16) from rubber retainer (15).
NOTE₆: For added leverage, insert a rod through central body (10) as needed.
- J-1.11) Unscrew rubber mandrel (11) from valve body (29).
- J-1.12) Remove rubber mandrel assembly and disassemble:
 J-1.12.1) Remove elements (13, 14), rubber spacers (12) and rubber retainer (15) from rubber mandrel (11).
- J-1.13) Unscrew and remove valve body (29) from central body (10).
 J-1.13.1) Remove o-ring (41) from valve body (29).



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: A

Revision Date:
07/06/2023

Authored by: J.Anderson

Approved by: K.Plunkett

J) DISASSEMBLY (cont'd)

- J-1.14) Unscrew and remove central body (10) from hold down body (6).
- J-2) Unclamp and remove top sub (1) from vise. Clamp lower end of inner mandrel (2) in vise.
 - CAUTION:** Do NOT wrench or clamp on seal surface.
 - J-2.1) Unscrew and remove set screws (36) from top sub (1).
 - J-2.2) Unscrew and remove top sub (1) from inner mandrel (2).
 - J-2.2.1) Remove o-ring (40) from top sub (1).
 - J-2.3) Unscrew and remove hold down extension (4) from hold down body (6).
 - J-2.3.1) Remove o-ring (44) from hold down extension (4).
 - J-2.4) Move lower strap retainer (7) downwards temporarily out of way.
 - J-2.5) Unscrew and remove hold down cap (5) from hold down body (6).
 - J-2.6) Unscrew and remove flat head cap screws (33) from hold down body (6).
 - J-2.7) Remove hold down straps (31) from hold down body (6).
 - J-2.8) Remove button springs (26) from hold down buttons (30).
 - J-2.9) Remove hold down buttons (30) from hold down body (6) with button removal tool (T2).
 - J-2.9.1) Remove o-rings (38) from hold down buttons (30).
 - J-2.10) Remove hold down body (6) from inner mandrel (2).
 - J-2.10.1) Remove o-rings (42, 43) from hold down body (6).
 - J-2.11) Remove lower strap retainer (7) from inner mandrel (2).
 - J-2.12) Unscrew and remove compensating mandrel (8) from seal receptacle (28).
 - CAUTION:** Do NOT wrench or clamp on seal surface.
 - J-2.13) Remove compensating piston (9) from compensating mandrel (8).
 - J-2.13.1) Remove o-rings (45, 46) from compensating piston (9).
- J-3) Unclamp and remove inner mandrel (2) from vise.
 - J-3.1) Remove seal receptacle (28) from inner mandrel (2).
 - J-3.1.1) Unscrew and remove seal retainer (27) from seal receptacle (28).
 - J-3.1.2) Remove o-rings (41, 42) from seal receptacle (28).
 - J-3.1.3) Remove quad seal (24) from seal retainer (27).

K) ASSEMBLY

NOTE: Clean and inspect all parts. Replace all worn and damaged parts. Install parts in proper order, orientation and tighten/torque all connections properly.

CAUTION: To ensure tool operates properly, install o-rings in o-ring grooves **NOT** thread reliefs (Fig. 2).

NOTE: Apply KOPR-KOTE® anti-seize lubricant (T3) on STUB ACME and drill pipe connections when making up connections.

K-1) Assemble seal receptacle assembly and install:

- K-1.1) Install quad seal (24) in groove in seal retainer (27).
- K-1.2) Install o-rings (41, 42) in o-ring grooves in seal receptacle (28).
- K-1.3) Screw seal retainer (27) onto seal receptacle (28).
 - CAUTION:** Do not rip or tear quad seal during installation.
- K-1.4) Install seal receptacle (28) and assembly onto inner mandrel (2).




Fig. 2



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: A

Revision Date:
07/06/2023

Authored by: J.Anderson

Approved by: K.Plunkett

K) ASSEMBLY (cont'd)

K-2) Clamp lower end of inner mandrel (2) in vise.

CAUTION₆: Do NOT wrench or clamp on seal surface.

K-2.1) Assemble compensating mandrel assembly and install:

K-2.1.1) Install o-rings (45, 46) into o-ring grooves in compensating piston (9).

K-2.1.2) Install compensating piston (9) onto compensating mandrel (8).

NOTE₉: Compensating piston **MUST** be installed in correct direction (Fig. 3).

CAUTION₉: Do not rip or tear o-ring during installation.

K-2.1.3) Screw compensating mandrel (8) into seal receptacle (28).

CAUTION₉: Do not rip or tear o-ring during installation.

K-2.2) Place strap retainer (7) onto inner mandrel (2) – it will be installed in later step.

K-2.3) Assemble hold down body assembly and install:

K-2.3.1) Install o-rings (42, 43) into o-ring grooves in hold down body (6).

K-2.3.2) Install hold down body (6) onto inner mandrel (2).

K-2.4) Assemble hold down buttons and install:

K-2.4.1) Install o-rings (38) into o-ring grooves in hold down buttons (30).

K-2.4.2) Install hold down buttons (30) into hold down body (6) (Fig. 4).

CAUTION₉: Do not rip or tear o-rings during installation.

K-2.4.3) Align slots in hold down buttons (30) with slot in hold down body (6).
Install button springs (26) into hold down buttons (30).

NOTE₁₀: Install two (2ea) hold down button springs per hold down button (Fig. 5).

K-2.4.4) Set hold down straps (31) in slots in hold down buttons (30) and hold down body (6) (Fig. 5).

K-2.4.5) Screw flat head cap screws (33) into hold down body (6) securing hold down straps (31) (Fig. 5).

K-2.5) Install strap retainer (7) onto hold down body (6) capturing lower ends of hold down straps (31).

K-2.6) Screw hold down cap (5) onto hold down body (6) capturing upper ends of hold down straps (31).

K-2.7) Install o-ring (44) in o-ring groove in hold down cap (4).

K-2.8) Screw hold down extension (4) into hold down body (6).

K-2.9) Install o-ring (40) into o-ring groove in top sub (1).

K-2.10) Screw top sub (1) onto inner mandrel (2).

CAUTION₉: Do not rip or tear o-ring during installation.

K-2.11) Screw set screws (36) into top sub (1).

K-3) Unclamp and remove inner mandrel (2) from vise. Clamp top sub (1) in vise.

K-3.1) Screw central body (10) onto hold down body (6).

CAUTION₉: Do not rip or tear o-ring during installation.

K-3.2) Install o-ring (41) into o-ring groove in valve body (29).

K-3.3) Screw valve body (29) into central body (10).

CAUTION₉: Do not rip or tear o-ring during installation.




Fig. 3



Fig. 4



Fig. 5



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: A

Revision Date:
07/06/2023

Authored by: J.Anderson

Approved by: K.Plunkett

K) ASSEMBLY (cont'd)

K-3.4) Assemble rubber mandrel assembly and install:

K-3.4.1) Install rubber retainer (15), rubber spacers (12), and elements (13, 14) onto rubber mandrel (11).

K-3.4.2) Install rubber mandrel assembly onto inner mandrel (2).

K-3.4.3) Screw rubber mandrel (11) into valve body (29).

CAUTION₉: Do not rip or tear o-ring during installation.

K-3.5) Screw lower cone (16) into rubber retainer (15).

K-3.6) Assemble drag block body assembly and install:

K-3.6.1) Install lower slips (17) and lower slip springs (25) into drag block body (18). Wedge slips outward.

NOTE₁₁: Install two (2ea) slip springs per slip (Fig. 6).

K-3.6.2) Install lower slip support (32) into drag block body (18).

K-3.6.3) Align hole in lower slip support (32) with threaded hole in drag block body (18). Screw socket cap screw (34) into drag block body (18). Remove wedges.

K-3.6.4) Install drag block body (18) and assembly onto rubber mandrel (11).

K-3.7) Screw rubber mandrel cap (19) onto rubber mandrel (11).

K-3.8) Install drag blocks (22) and drag block springs (3) into drag block body (18). Compress drag blocks (22) with drag block assembly tool (T1).

NOTE₁₂: Install five (5ea) drag block springs per drag block (Fig. 7).

K-3.9) Install drag block retainer (21) onto drag block body (18) capturing ends of drag blocks (22).

K-3.10) Screw J-body (20) onto drag block body (18) (**NOTE₄:** Left-hand threads).

K-3.11) Screw set screws (35) into J-body (20). Release drag blocks (22).

K-3.12) Install o-ring (39) into o-ring groove in bottom sub (23).

K-3.13) Screw bottom sub (23) onto inner mandrel (2).

NOTE₃: Drag block body assembly must be free to rotate.

CAUTION₉: Do not rip or tear o-ring during installation.

K-3.14) Screw set screws (37) into bottom sub (23). Move J-body (20) as needed to access threaded holes in bottom sub (23).

K-4) Unclamp top sub (1) from vise and remove assembled tool.




Fig. 6



Fig. 7



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: **A**

Revision Date:
07/06/2023

Authored by: J.Anderson

Approved by: K.Plunkett

L) PARTS LIST

ITEM	QTY	DESCRIPTION	MATERIAL	P/N 61362XLS
1	1	TOP SUB	DLMS110	61355615
2	1	MANDREL	DLMS110	61355215
3	30	DRAG BLOCK SPRING		9100900
4	1	HOLD DOWN EXTENSION	DLMS110	61355310
5	1	HOLD DOWN CAP	DLMS110	61362X370
6	1	HOLD DOWN BODY	DLMS110	61360321
7	1	STRAP RETAINER	DLMS60	61362X650
8	1	COMPENSATING MANDREL	DLMS110	61355240
9	1	COMPENSATING PISTON	DLMS110	61355710
10	1	CENTRAL BODY	DLMS110	61355381
11	1	RUBBER MANDREL	DLMS110	61362X220
12	2	RUBBER SPACER	DLMS35	60262X840
13	1	ELEMENT	80 DURO NITRILE	60262X512
14	2	ELEMENT	90 DURO NITRILE	60262X513
15	1	RUBBER RETAINER	DLMS110	61362X850
16	1	LOWER CONE	DLMS110	61360420
17	4	CARBIDE LOWER SLIP	DLMS110	60055135C
18	1	DRAG BLOCK BODY	DLMS110	61362X335
19	1	RUBBER MANDREL CAP	DLMS60	60055230
20	1	J-BODY	DLMS110	61355341
21	1	DRAG BLOCK RETAINER	DLMS60	61362X910
22	6	CARBIDE DRAG BLOCK	DLMSDB4	9045900C
23	1	BOTTOM SUB	DLMS110	61355635
24	1	QUAD SEAL	90 DURO NITRILE	61355520
25	8	LOWER SLIP SPRING		7155901
26	12	BUTTON SPRING		61355975
27	1	SEAL RETAINER	DLMS80	61355530
28	1	SEAL RECEPTACLE	DLMS110	61355730
29	1	VALVE BODY	DLMS110	61362X350
30	6	CARBIDE HOLD DOWN BUTTON	DLMS110	61357140C
31	3	HOLD DOWN STRAP	DLMSFB4	61355360
32	1	LOWER SLIP SUPPORT	DLMS110	61362X912
33	3	5/16-18 UNC X 1/2 FLAT HEAD SOCKET CAP SCREW	STEEL	FHSC031C050
34	1	5/16-18 UNC X 1/2 SOCKET CAP SCREW	STEEL	SCS031C050
35	4	5/16-18 UNC X 1/2 SOCKET SET SCREW	STEEL	SSS031C050



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: **A**

Revision Date:
07/06/2023

Authored by: J.Anderson

Approved by: K.Plunkett

L) PARTS LIST (cont'd)

ITEM	QTY	DESCRIPTION	MATERIAL	P/N 61362XLS
36	3	3/8-16 UNC X 3/8 SOCKET SET SCREW	STEEL	SSS037C037
37	4	3/8-16 UNC X 1/2 SOCKET SET SCREW	STEEL	SSS037C050
38	6	224 O-RING	90 DURO NITRILE	90224
39	1	229 O-RING	90 DURO NITRILE	90229
40	1	231 O-RING	90 DURO NITRILE	90231
41	2	235 O-RING	90 DURO NITRILE	90235
42	2	236 O-RING	90 DURO NITRILE	90236
43	1	241 O-RING	90 DURO NITRILE	90241
44	1	334 O-RING	90 DURO NITRILE	90334
45	1	339 O-RING	90 DURO NITRILE	90339
46	1	342 O-RING	90 DURO NITRILE	90342

REDRESS KIT (RDK)	61362X050
ASSEMBLED WEIGHT	189 LBS

L-1) ELASTOMER TRIM OPTIONS

NOTE₁₃: For temperature range, refer to Elastomer Trim Temperature Guide.

L-1.1) HSN

ITEM	QTY	DESCRIPTION	MATERIAL	P/N 61362XLSH
13	1	ELEMENT	80 DURO HSN	60262X512H
14	2	ELEMENT	90 DURO HSN	60262X513H
24	1	QUAD SEAL	90 DURO HSN	6135520H
38	6	224 O-RING	90 DURO HSN	90224H
39	1	229 O-RING	90 DURO HSN	90229H
40	1	231 O-RING	90 DURO HSN	90231H
41	2	235 O-RING	90 DURO HSN	90235H
42	2	236 O-RING	90 DURO HSN	90236H
43	1	241 O-RING	90 DURO HSN	90241H
44	1	334 O-RING	90 DURO HSN	90334H
45	1	339 O-RING	90 DURO HSN	90339H
46	1	342 O-RING	90 DURO HSN	90342H

REDRESS KIT (RDK)	61362X050H
-------------------	------------



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689

Revision: **A**

Revision Date:
07/06/2023

Authored by: J.Anderson

Approved by: K.Plunkett

L) PARTS LIST (cont'd)

L-1.2) VITON

ITEM	QTY	DESCRIPTION	MATERIAL	P/N 61362XLSV
13	1	ELEMENT	80 DURO VITON	60262X512V
14	2	ELEMENT	90 DURO VITON	60262X513V
24	1	QUAD SEAL	90 DURO VITON	61355520V
38	6	224 O-RING	90 DURO VITON	90224V
39	1	229 O-RING	90 DURO VITON	90229V
40	1	231 O-RING	90 DURO VITON	90231V
41	2	235 O-RING	90 DURO VITON	90235V
42	2	236 O-RING	90 DURO VITON	90236V
43	1	241 O-RING	90 DURO VITON	90241V
44	1	334 O-RING	90 DURO VITON	90334V
45	1	339 O-RING	90 DURO VITON	90339V
46	1	342 O-RING	90 DURO VITON	90342V

REDRESS KIT (RDK)		61362X050V
-------------------	--	------------



HD RETRIEVABLE PACKER LEFT-HAND AUTO 6" X 2-3/8" (24.5#)

Manual No:
DL-613-6000-1689



Revision: **A**

Revision Date:
07/06/2023

Authored by: *J.Anderson*

Approved by: *K.Plunkett*

M) TECHNICAL ILLUSTRATION



N) REVISION HISTORY

DATE	REVISION	DESCRIPTION OF CHANGES	REVISED BY	APPROVED BY
07/06/2023	A	Created manual	-	-