

AS-5 PACKER

The **AS-5 Packer** is a compression set tool with a J-slot to control pack-off. It is run above other packers - such as the AS-III Packer - to selectively treat, produce or inject in multiple zone completions. It is also used to isolate casing hole perforations. This packer features a large by-pass area to prevent swabbing when running and retrieving. When releasing, the valve allows debris to be washed from the upper slips.

Special Features

- Large internal by-pass
- Mechanical slips vs. hydraulic buttons
- Additional J-slot arrangements available

Product Specifications

Casing		Recommended Hole Size (inches)	Tool OD (inches)	Tool ID (inches)	Thread Connections Box Up / Pin Down	Part Number
Size (inches)	Weight (lbs/ft)					
4-1/2	9.5 - 13.5	3.920 - 4.090	3.750	1.94	2-3/8 EUE	60845
5-1/2	14.0 - 20.0	4.778 - 5.012	4.625	2.00	2-3/8 EUE	60855
				2.38	2-7/8 EUE	60856
	20.0 - 23.0	4.670 - 4.778	4.500	2.00	2-3/8 EUE	60857
				2.38	2-7/8 EUE	60859
7	17.0 - 26.0	6.276 - 6.538	6.000	2.50	2-7/8 EUE	60872
				3.00	3-1/2 EUE	60874
	26.0 - 32.0	6.094 - 6.276	5.875	2.50	2-7/8 EUE	60870

NOTE: All pricing includes standard Nitrile trim. Carbide, other sizes, connections, and J-slot configurations are available upon request.

