

TYPE DL-IB TANDEM TENSION PACKER

The **Type DL-IB Tandem Tension Packer** is an economical, compact, low-pressure, tension set, isolation packer used in casing or perforations and multi-zone injection installations. This packer runs with a tension set packer below. It can be run with the J-pins in the un-jayed position or in the jayed position. In the un-jayed position, applying tension shears the shear pins and allows pack-off.

If run in the jayed position, the DL-IB Tandem Tension Packer must be used in

conjunction with an ASI-X Packer. Set down weight shears the pins; left-hand rotation and applied tension will set the tool.

Special Features

- Economical
- Run in jayed position, or un-jayed position
- Optional J-configurations



Product Specifications

Casing		Recommended Hole Size (inches)	Tool OD (inches)	Tool ID (inches)	Thread Connections Box Up / Pin Down	Part Number
Size (inches)	Weight (lbs/ft)					
3-1/2	7.7 - 10.3	2.922 - 3.068	2.781	1.53	1.900 EUE	43635
4-1/2	9.5 - 11.6	4.000 - 4.090	3.844	1.94	2-3/8 EUE	43644
				2.38	2-7/8 EUE	43646
	9.5 - 13.5	3.920 - 4.090	3.750	1.50	2-3/8 EUE	43647
				1.94	2-3/8 EUE	43645
15.1	3.826	3.650	1.94	2-3/8 EUE	43643	
5	15.0 - 18.0	4.276 - 4.408	4.125	1.94	2-3/8 EUE	43651
				2.38	2-7/8 EUE	43650
	18.0 - 20.8	4.156 - 4.276	4.000	1.94	2-3/8 EUE	43652
5-1/2	13.0 - 15.5	4.950 - 5.044	4.781	2.00	2-3/8 EUE	43655
				2.44	2-7/8 EUE	43656
	13.0 - 20.0	4.778 - 5.044	4.750	3.00	3-1/2 EUE	43653
				2.00	2-3/8 EUE	43657
	15.5 - 20.0	4.778 - 4.950	4.641	2.44	2-7/8 EUE	43658
2.00				2-3/8 EUE	43654	
7	17.0 - 23.0	6.366 - 6.538	6.125	2.00	2-3/8 EUE	43671
				2.44	2-7/8 EUE	43670
	17.0 - 26.0	6.276 - 6.538	6.000	3.00	3-1/2 EUE	43673
7-5/8	24.0 - 29.7	6.875 - 7.025	6.672	2.44	2-7/8 EUE	43675
9-5/8	32.3 - 43.5	8.755 - 9.001	8.500	3.00	3-1/2 EUE	43696
	43.5 - 53.5	8.535 - 8.755	8.250	2.50	2-7/8 EUE	43695

NOTE: All pricing includes standard Nitrile trim. Other sizes and connections available upon request.